



MA

DISCIPLINED DURABILITY.



15 MPH [24 KM/H]
TOP SPEED




CUSTOMIZABLE
FEATURES



6,000lb [2,722 kg]
MAX DRAWBAR



POWER
STEERING



TUG[®] MA

The TUG™ MA stands strong with trusted durability and reliability, even in the most demanding environments. Experience effortless maneuvering with power steering, ensuring smooth navigation through any task. Equipped with a heavy-duty axle, this tractor can handle heavy loads with ease. Several engine and hitch options offer versatility to best suit your specific operational needs. When reliability matters most, the TUG MA delivers the proven performance, and lasting durability operators depend on.

SHARED FEATURES

- 12V, Negative Ground Electrical System
- Standard E-Hitch
- LED Headlights and Taillights
- Black Lap Belts

OPTIONAL FEATURES

- Economy Cab
- Full Cab
- Backup Alarm
- Front Brakes
- Snowplow
- Additional Hitches to Fit Custom Specifications



	FORD MSG-425 EFI GASOLINE	DEUTZ D2.9L DIESEL TIER IV FINAL	DEUTZ D2.9L DIESEL (NON EMISSIONS REGULATED)	KUBOTA WG2503G
CHASSIS POWER				
Type	Water-Cooled, EFI, 4 Cylinder	Water-Cooled, Common Rail, In-Line, 4 Cylinder		Vertical, Water-Cooled, In Line, 4 Cylinder
Fuel	Gas (External Fuel Pump) / LPG	ULSD	ULSD, LSD	Gas (In-Tank Fuel Pump)
Displacement	153 CID [2.5 L]	177 CID [2.9 L]		152 CID [2.5 L]
Governed RPM w/ Full Load	2,600 RPM			
Net Brake hp at Governed Speed	69 hp [51.5 kW]	49 hp [36.5 kW]		54 hp [40.2 kW]
Torque	143 lb-ft [193.8 Nm] @ 2,400 RPM	108 lb-ft [146.4 Nm] @ 1,600 RPM		126 lb-ft [170.8 Nm] @ 1,800 RPM
Gauges	Hour Meter and Mechanical Fuel Gauge			MVP LCD Display on Dash
Parking Brake	Disc on Rear Axle			Disc on Transmission Output Shaft
Transmission	GM 4LHD (w/ Gen III Electronic Valvebody)			
Shifter	Electronic FNR on Dash			
DIMENSIONS				
Width	55 in [1,397 mm]			
Length (w/ Standard Rear Hitch)	120 in [3,048 mm]			
Length (w/ Front and Rear Hitch)	126 in [3,200 mm]			
Length (w/o Hitches)	113 in [2,870 mm]			
Height (w/ Cab)	81.5 in [2,070 mm]			
Height (w/o Cab)	63.5 in [1,613 mm]			
Wheelbase	59 in [1,499 mm]			
Ground Clearance	6.5 in [165 mm]			
Outside Turning Radius	115 in [2,921 mm]			
Minimum Weight	3,750 lbs [1,701 kg]			
Standard Weight	3,750 lbs [1,701 kg]			
Maximum Weight	7,500 lbs [3402 kg]			
STANDARD EQUIPMENT				
Drive Axle	Heavy Duty 6,000 lb [2,721.6 kg] Capacity Axle w/ Drop Box			
Brakes	Dual Calipers on each Rear Wheel and Split Hydraulic Assist Master Cylinder; Lever Operated Parking Brake			
Suspension	Front: Leaf Springs; Rear: Rubber Mount			
Hitch	Rear E-Hitch at 13.5 in [343 mm] from ground			
	MA30	MA40	MA50	MA60
PERFORMANCE				
Drawbar Pull	3,000 lb [1,360.6 kg]	4,000 lb [1,814.4 kg]	5,000 lb [2,268 kg]	6,000 lb [2,721.6 kg]
GVW	3,750lb [1,701 kg]	5,000 lb [2,268 kg]	6,250 lb [2,835 kg]	7,500 lb [3,401.9 kg]
Tires	Front: 6.9 in X 9 in, 6-Ply Rating; Rear: 8 in X 16 in, 8-Ply Rating			