




# TANKER TRUCK

REFILL EFFICIENTLY



# TANKER TRUCK

The Tanker Truck (TT4000) provides customized deicing equipment solutions for airport operations, enhancing efficiency by reducing refill times and minimizing deicer mileage. With three fluid storage tanks offering a total capacity of 4000 gallons, including two linked 1500-gallon tanks for deicing fluid and a 1000-gallon tank for anti-ice fluid, the TT4000 can refill up to four MT35P9 deicers on the same run. Constructed from 12 gauge, glycol-specific A304 stainless steel, these tanks ensure fluid can be stored at any temperature, providing unmatched durability and versatility. The Tanker Truck features an anti-ice, positive displacement, self-priming diaphragm pump that transfers at a fluid rate of 75 GPM as well as a centrifugal style deice pump that transfers at a fluid rate of 200 GPM, making fluid transfer quick and convenient.

As the only deicing refill truck on the market, the Tanker Truck is the perfect addition to any deicing fleet looking to increase productivity.

### SHARED FEATURES

- Power Steering
- 12V negative Ground
- 160 Amp Alternator



FREIGHTLINER M2 106	
CHASSIS POWER	
Type	Cummins 6 Cylinder Turbocharged L9
Fuel	Fuel Cell Capacity: 100 Gal [379 L], USLD
DEF Capacity	6 Gal [22.7 L]
Displacement	543 CID [8.9 L]
Governed RPM w/ Full Load	2,200 RPM
Peak hp at Governed Speed	350 hp @ 2,200 RPM
Torque	1050 ft-lb @ 1,200 RPM
Gradeability	8%
PTO Speed	1000 RPM / 1400 RPM
PTO	Muncie A20A1008HX3BB9X
Block Heater	Phillips-Temro T 1000 Watt / 115V
Rear Differential	User Lockable
Parking Brake	Air Operated on Dash
Transmission	Allison 3000 RDS with PTO (LH)
Shifter	Push-Button
DIMENSIONS	
Width	102 in [2,590.8 mm]
Length	29 ft [8.8 m]
Height	118 in [2997.2 mm]
Wheelbase	204 in [5,181.6 mm]
Ground Clearance	10 in [254 mm]
STANDARD EQUIPMENT	
Brakes	Pneumatic
Suspension	Front and Rear: Leaf Springs
Hitch	16 in [406.4 mm] F&R pin style
PERFORMANCE	
Maximum Governed Speed	30 mph [48 km/h]
EPA Tier Level	US Tier IV
Deice Pump	Gorman Rupp centrifugal style fluid pump with 3 inch inlet and outlet providing 200 GPM at 25 PSI. Pump is hydraulically driven.
Anti-ice Pump (Diaphragm)	Hardi six diaphragm positive displacement radial pump 2 inch inlet and a 1 1/4 inch outlet providing 75 GPM of fill rate. Pump is hydraulically Driven.
De-ice Fluid Tank	Dual 1,500 Gal [5,678 L] Stainless Steel
Anti-ice Fluid Tank	Single 1000 Gal [3,785 L] Stainless Steel
De-ice Hose Reel	25 ft 2 in Diameter with 12V Retract
Anti-ice Hose Reel	25 ft 2 in Diameter with 12V Retract
Suction Fill	RH Side with External Pump
Axle Ratings	Front: 20,000 lb [9,072 kg] Rear: 34,000 lb [15,422 kg]
Tires	Front: Michelin XZU-32 315/80R22.5 Rear: Michelin X Works 315/80R22.5

