





## MA

## DISCIPLINED DURABILITY.









## TUG - MA

The TUG™ MA stands strong with trusted durability and reliability, even in the most demanding environments. Experience effortless maneuvering with power steering, ensuring smooth navigation through any task. Equipped with a heavy-duty axle, this tractor can handle heavy loads with ease. Several engine and hitch options offer versatility to best suit your specific operational needs. Heighten your productivity with the TUG MA, where durability, reliability, and flexibility come together to set the new standard in the world of ground support equipment.



CHASSIS POWER		
Ford MSG-425 EFI Gasoline		
Fuel & Compatible Fuel (Type & Quantity)	Gas / CNG / LPG	
Displacement (Size of Engine)	153 CID (2.5 L)	
Governed RPM with Full Load	2,600	
Net Brake HP at Governed RPM	69 (52 kW)	
Transmission	GM 4LHD (with Gen III Electronic Valvebody)	
Torque	143 lb ft (194 Nm) @ 2,400 RPM	
Kubota WG2503G		
Fuel & Compatible Fuel (Type & Quantity)	Gas	
Displacement (Size of Engine)	152 CID (2.5 L)	
Governed RPM with Full Load	2,600	
Net Brake HP at Governed RPM	54 (40 kW)	
Transmission	GM 4LHD (with Gen III Electronic Valvebody)	
Torque	126 lb ft (171 Nm) @ 1,800 RPM	
Deutz D2.9L		
Fuel & Compatible Fuel (Type & Quantity)	Ultra Low Sulfer Diesel	
Displacement (Size of Engine)	177 CID (2.9 L)	
Governed RPM with Full Load	2,600	
Net Brake HP at Governed RPM	49 (36.5 kW)	
Transmission	GM 4LHD (with Gen III Electronic Valvebody)	
Torque	108 lb ft (148 Nm) @ 1,600 RPM	

DIMENSIONS	
Width	55" (1,397 mm)
Wheelbase	59" (1,499 mm)
Height (Less Cab)	63.5" [1,613 mm]
Height (With Cab)	84" (2,134 mm)
Standard Weight	3,750 lbs (1,701 kg)
Minimum Weight	3,750 lbs (1,701 kg)
Maximum Weight	7,500 lbs (3,402 kg)
Length (without Hitches)	113" (2,870 mm)
Ground Clearance	6.5" (165 mm)
Outside Turning Radius	115" (2,920 mm)

PERFORMANCE		
Ford MSG-425 EFI Gasoline		
Top Speed	15 mph (24.1 km/h)	
Туре	Water-Cooled, 4 Cylinder EFI	
Kubota WG2503G		
Top Speed	15 mph (24.1 km/h)	
Туре	Water-Cooled, 4 Cylinder, Vertical In Line	
Deutz D2.9L		
Top Speed	15 mph (24.1 km/h)	
EPA Tier / Certification Level	Tier 4F	
Туре	Water-Cooled, 4 Cylinder, Common Rail In Line	

